



# CIMGLIDE® 68

*Machine Tool Slideway Lubricant*



## Product Application Guide

**CIMGLIDE® 68** is a specially formulated MACHINE TOOL lubricant for all horizontal slideways. Meeting the Cincinnati Machine P47 Specification, it combines mineral oil and extreme pressure additives to assist in eliminating stick-slip to ensure machines run at their optimal performance.

**Suitable for use in the following machine tool applications:** Horizontal slideways, Feed mechanisms (in accordance with manufacturers specification), Tables, Gear boxes, Hydraulic systems

### FEATURES AND BENEFITS

- The lubricant package used in CIMGLIDE® 68 is designed for minimal impact on water based metalworking fluids
- Good demulsibility allows for easy removal of tramp oil to maximize water based metalworking fluid life
- Reduces wear and stick-slip of slideways and screws
- Strong adhesion and chemical stability to improve machine tool productivity
- Long service life and protection from corrosion
- Uses high grade materials to minimize odors and protect against fungus and bacteria

### TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

ISO Viscosity Grade: .....	68
Specific Gravity: .....	0.8820
Flash Point (°C): .....	224
Pour Point (°C): .....	-35.0
Viscosity, (cSt), -40 °C: .....	68.0
Viscosity Index: .....	102
Copper Strip Corrosion: .....	1a

**PACKAGING:** 20 litre pails, 200 litre drums, and bulk containers

Contact Details:

For additional information on **CIMGLIDE® 68** refer to its MSDS or contact CIMCOOL Technical Services e-mail: [info@cimcoolapac.com](mailto:info@cimcoolapac.com) · Reprints/updates: [www.cimcoolapac.com](http://www.cimcoolapac.com)  
This product is sold by CIMCOOL Fluid Technology, a division of Milacron LLC. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.