

CIMSPIN 10

Spindle and Hydraulic Oil



Product Application Guide

CIMSPIN 10 is a spindle and hydraulic oil designed for high speed spindle bearings in precision grinders and machine tools requiring low-viscosity oils. **CIMSPIN 10** is blended with premium base oils and special additive packages to exceed the needs of modern manufacturing.

FEATURES AND BENEFITS

- Extends spindle life and reduces wear - Provides excellent lubricity to minimize wear under high load conditions including wear caused by spindle wobble from unbalanced loads.
- Multi-metal compatibility - Protects ferrous and non-ferrous metals from corrosion.
- Good oxidation resistance - Excellent oxidation stability to provides long service life.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Iso Viscosity Grade	10
Specific Gravity.....	0.875
Viscosity@40°C	10
Flash Point(°C).....	150
Pour Point(°C)	-20

PACKAGING: 20 litre pails, 200 litre drums, and bulk containers

Contact Details:

For additional information concerning **CIMSPIN 10**, refer to its MSDS or contact CIMCOOL® Technical Service Support at +82 52 239 2333. Reprints/updates of this Product Information Flyer (PIF) can be found on our web site, www.cimcool.com or from your CM Fluid Technology representative.

This product is sold by Cimcool Korea, a Milacron Marketing Company, Cincinnati, Ohio 45209. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.